



Simply **brighter.**

SPECIFICATION

LedNEON LF15S-HB-CC-RGB-RGBW



Ver. 3.1

Table of Contents

Introduction		03
1. Specifications & Parameters		04
1.1 Dimensions of Light	4	
1.2 Technical Parameters	4	
1.3 Optical Parameters	4	
2. Functions & Features		05
2.1 Product Features	5	
2.2 Minimum Bend Diameter	5	
3. Types of Connector		05
3.1 Injection-Moulded Connector	5	
3.2 Dual Injection-Moulded Connector	7	
3.3 Sleeve Connector	8	
3.4 Snap Connector	9	
3.5 Anti-wicking Ferrule	10	
3.6 Male & Female Connector	10	
4. Compatible Control System		11
4.1 LT-200	11	
4.2 LT-800 & LT-1809	11	
4.3 LT-600	11	
5. Mounting Profile		12
5.1 Standard Aluminum Profile	12	
5.2 Plastic Profile	12	
5.3 Spring Clip Aluminum Profile	13	
5.4 Bendable Stainless Steel Profile	13	
5.5 Cable Exit Oriented Aluminum Profile (Applicable to Injection-moulded Connector Only)	14	
5.6 Corner Aluminum Profile (Applicable to Injection-moulded Connector Only)	14	
5.7 Recessed Mounting Profile	15	
6. Appendix		16
6.1 Certificate	16	
6.2 Third-Party Test Report	16	
6.3 Reliability Test of Light	16	
6.4 (X,Y) Chromaticity Diagram	17	

Introduction

LF15S-HB-CC-RGB-RGBW is a member of the LedNEON series embodied all the benefits of LF15A and LF15B with the addition of DMX addressable technology, generating advanced chasing and programmable scenes and complete animated visual effects.

LF15S-HB-CC-RGB-RGBW is UL/cUL, CE i TUV and RoHS compliant. Moreover, it has passed rigorous environmental resistance, optical, mechanical and electrical tests in our lab under the support of advanced experimental equipments and technology to ensure it meets the requirements of harsh environments. Also it has passed relevant tests of thrid party inspection authority.


Fully encapsulated in the flexible PCV chamber by utilizing consumate extrusion technology, assembled with multiple patented connectors to achieve IP68 protection, easy for installation and applicable for various circumstances.

LF15S-HB-CC-RGB-RGBW features the capability of producing millions of colors and impressive animated effects when paired with DMX controller, also ultra flexibility and pliability with small bend diameter in curve bending shape.


Application:

1. Outdoor or Indoor Contour/Border Lighting
2. Architectural Outline/Decorative Lighting
3. Cove/Accent Lighting
4. Facade/Floor Lighting
5. Signage/Guide Lighting

1. Specifications & Parameters



1.1 Dimensions of Light



1.2 Technical Parameters

Technical Parameters

Article No.	C-FR-F15S-24CC	C-FR-F15S-24CC
Color	RGB	RGBW(2700K/3000K4000K)
IC Type	UCS2903	UCS2904
Working Voltage	DC24V	DC24V
Rated Power/m	12W	15W
LED Qty/m	56	56
LED Distance	17.8mm	17.8mm
Min. Cutting Unit	7LEDs (1 pixel)	7LEDs (1 pixel)
Min. Cutting Length	125mm (1unit)	125mm (1unit)
Continuous Length	15m (Dynamic Operating) 10m (Static Full Loading)	10m (Dynamic Operating) 5m (Static Full Loading)
Weight/m	325g	
Storage Temperature	-20 ~ 60°C	
Ambient Working Temperature	-20 ~ 45°C	
Ambient Installation Temperature	0 ~ 45°C	
IP Rating	IP68	


Note: For this product that over 12W per meter, full loading operating is not recommended.

1.3 Optical Parameters

Photometric Data

Article No.	C-FR-F15S-24CC(RGB/RGBW)	
LED Type	SMD	
Beam Angle 50%	120°	
Color	Wavelength	Lumen
Red	618-624nm	>40lm
Green	522-528nm	>100lm
Blue	468-474nm	>15lm
White	2725±145K	>100lm
	3045±175K	>100lm
	3985±275K	>100lm

Candle power distribution




2. Functions & Features


2.1 Product Features

1. High quality SMD LED & IC Chip.
2. UCS2903/2904 IC, SPI signal input, DMX512 signal compatible, DMX address writable or programmable.
3. UV & flame resistant construction(PVC).
4. Extremely flat profile and flush light surface.
5. High color consistency&smooth illumination with invisible light dots.
6. Flexible with 120mm minimum bending diameter.
7. Easy installation and assembly with DIY accessories for joining and terminating. 8.
- High IP rating(IP68).
9. The product IP rate is ultimately in line with properly applied IP rated connectors.
10. Environmentally friendly & energy efficient.

2.2 Minimum Bend Diameter



The light can only be bent laterally (opposite bend along to light surface).



Do not bend smaller than allowed minimum bend diameter.


3. Types of Connector


3.1 Injection-moulded Connector



Injection-moulded Front Connector (bottom)



Connects light to power supply with pre-installed bottom feed cable, IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.






Injection-moulded Front Connector (side)

Connects light to power supply with pre-installed side feed cable, IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.





Injection-moulded Front Connector (top end)

Connects light to power supply with pre-installed end feed cable, IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.



Injection-moulded End Cap


Pre-installed termination protection of the light, IP67.



Injection-moulded Jumper

Connects two pieces of lights together with a flexible cable. IP67. Injection-moulded connector. L available in 0.3~1m.


Maximum 8 Jumpers in 20m
Maximum 4 Jumpers in 10m



Injection-moulded T-feed

Connects two pieces of lights together with a T joint, energized from middle. IP67 Injection-moulded connector. L1 and L2 available in 0.15~0.5m. L3 available in 0.3~3m.

Maximum 8 T-feeds in 20m
Maximum 4 T-feeds in 10m





3.2 Dual Injection-moulded Connector




Dual Injection-moulded Front Connector (bottom)

Connects light to power supply with pre-installed bottom feed cable, IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.




Dual Injection-moulded Front Connector (side)

Connects light to power supply with pre-installed side feed cable, IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.




Dual Injection-moulded Front Connector (top end)

Connects light to power supply with pre-installed end feed cable, IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.



Dual Injection-moulded End Cap


Pre-installed termination protection of the light, IP68.



Dual Injection-moulded Jumper

Connects two pieces of lights together with a flexible cable. IP68 Dual Injection-moulded connector. L available in 0.3~1m.


Maximum 8 Jumpers in 20m
Maximum 4 Jumpers in 10m




Dual Injection-moulded T-feed

Connects two pieces of lights together with a T joint, energized from middle. IP68 Dual Injection-moulded connector. L1 and L2 available in 0.15~0.5m. L3 available in 0.3-3m.

Maximum 8 T-feeds in 20m
Maximum 4 T-feeds in 10m




3.3 Sleeve Connector



Sleeve Front Connector

Connects light to power supply. IP40 DIY connector. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.


Feed connector*1 (Three-pin)
PC cover*1
Anti-skidding clips*2



Sleeve End Cap

Termination protection of the light. IP40 DIY connector.


Shading Sheat*1
PC cover*1



Sleeve Middle Connector

Combine two pieces of lights together. DIY connector.


Pin connector*1 (Three-pin)
PC cover*2
Anti-skidding clips*4



Sleeve Jumper

Connects two pieces of lights together with a flexible cable. IP40 DIY connector. L available in 0.3m, 1m and 3m.


Double-end feed connector*1 (Three-pin)
PC cover*2
Anti-skidding clips*4



Sleeve Power T-feed

Connects two pieces of lights together with a T joint, energized from middle. IP40 DIY connector. L1 and L2 available in 0.3m.

T joint*1 (Three-pin)
PC cover*2
Anti-skidding clips*4




3.4 Snap Connector



Snap Front Connector(top end)

Connects light to power supply. IP67 DIY connector. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.


- Feed connector*1 (Three-pin)
- Silicone gasket*1
- U steel plate*1
- Anti-skidding clip*1
- PC Cover*1



Snap Front Connector(side right/left)

Connects light to power supply. IP67 DIY connector. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.


- Feed connector*1 (Three-pin)
- Silicone gasket*1
- U steel plate*1
- Anti-skidding clip*1
- PC Cover*1



Snap Front Connector(bottom)

Connects light to power supply. IP67 DIY connector. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.


- Feed connector*1 (Three-pin)
- Silicone gasket*1
- U steel plate*1
- Anti-skidding clip*1
- PC Cover*1



Snap End Cap

Termination protection of the light. IP67. DIY connector.


- Tail plug*1
- Silicone gasket*1
- U steel plate*1
- Anti-skidding clip*1
- PC Cover*1



Snap Jumper

Connects two pieces of lights together with a flexible cable. IP67 DIY connector. L available in 0.3m, 1m and 3m.


- Double-end feed connector*1 (Three-pin)
- Silicone gasket*2
- U steel plate*2
- Anti-skidding clip*2
- PC Cover*2



Snap Power T-feed

Connects two pieces of lights together with a T joint, energized from middle. IP67 DIY connector. L1 and L2 available in 0.3m.

- T joint*1 (Three-pin)
- Silicone gasket*2
- U steel plate*2
- Anti-skidding clip*2
- PC Cover*2




3.5 Anti-wicking Ferrule



Anti-wicking Ferrule

The anti-wicking ferrule is located at 115mm (± 5 mm tolerance) from the connector on the cable.

For protection against water ingress from inside of cable wire and hence damage the light.




3.6 Male & Female Connector



Male & female Connector

For plug and play cable junction, DIY or Pre-installed connector, IP68



4. Compatible DMX Control System (Recommended)

4.1 LT-200 Unit



1. SPI signal output, control light directly to achieve max.540 lighting effects.
2. Support third-party DMX 512 interface, it can be realized DMX management mode, invoke controller' s most function by DMX console.
3. It can work as DMX-SPI decoder, using DMX 512 console to control every channel and program new changing effect.

Suitable for controlling maximum 100m by series connection and each length maximum 15m.

4.2 LT-800 & LT-DMX-1809 Unit



1. LT-1809 decoder works to convert DMX512 digital signal to SPI (TTL) digital signal, realizing the function of 0~100% dimming or editing all sorts of change effect.
2. LT-800 DMX512 controller works with LT-1809 decoder to control lights .
3. Each LT-800 DMX512 controller can control max. 32 sets LT-1809 decoders.

Suitable for relatively large projects; each decoder can control max. 15m lights.

4.3 LT-600 Unit



1. Offline SD card store request programme. Ethernet real time computer control via synchronous display.
2. DMX 512 and SPI signal outputs are optional; can be connected with DMX console to form lighting control network.
3. Extra large control capability, 16 channels signal output, max. control 30720 pixels.

Suitable for large projects; each channel can control max. 120m lights, each LT-600 can control around 1600m lights.


Note:

The Pixel Addressable Light series allows precise control of every cutting increment. To ensure IC chips receive strong control signals, please adhere to the parameters listed below.

- 1) To ensure strong signal the 3-wire signal cable should not exceed 10m.
- 2) For cable lengths longer than 10m, a signal amplifier must be used for strong signal transmission. Please ask our technical team for more details.


5. Mounting Profile

5.1 Standard Aluminum Profile




Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.

Installation Way




Model	W*H(mm)	Standard Length (mm)	L1 (mm)	L2 (mm)	Screw Hole (mm)	Hole Number
F15-A/PL	13.8*22	35	17.5	/	$\Phi 3.5$	1
		500	50	200	$\Phi 3.5$	3
		1000	100	200	$\Phi 3.5$	5
		2000	100	200	$\Phi 3.5$	10

5.2 Plastic Profile




Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.

Installation Way




Model	W*H(mm)	Standard Length (mm)	L1 (mm)	L2 (mm)	Screw Hole (mm)	Hole Number
F15-P/PL	14*24	500	50	200	$\Phi 3.5$	3
		1000	100	200	$\Phi 3.5$	5
		2000	100	200	$\Phi 3.5$	10

5.3 Spring Clip Aluminum Profile




Note: Unless otherwise stated, the tolerance of the profile is ± 0.5 mm.

Installation Way




Model	W*H(mm)	Standard Length(mm)	L1(mm)	L2(mm)	L3(mm)	L4(mm)	Hole Screw(mm)	Hole Number	Clip Number
F15-SCA/PL	16.2*25.6	35	17.5	/	5	25	Φ3.5	2	1
		500	25	225	50	200	Φ3.5	3	3
		1000	25	237.5	100	200	Φ3.5	5	5
		2000	25	243.8	100	200	Φ3.5	10	9


5.6 Bendable Stainless Steel Profile



Note: Unless otherwise stated, the tolerance of the profile is ± 0.2 mm.



5.5 Cable Exit Oriented Aluminum Profile (Applicable to Injection-moulded Connector Only)



Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.



Bottom Feed



Middle Feed




Side Feed From Left



Side Feed From Right


5.6 Corner Aluminum Profile (Applicable to Injection-moulded Connector Only)



Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.



L Shape



T Shape



Outward L Shape





Inward L Shape




X Shape

5.7 Recessed Mounting Profile



Note: Unless otherwise stated, the tolerance of the profile is ± 0.5 mm.

Installation Way



Model	W*H(mm)	Standard Length (mm)	L1 (mm)	L2 (mm)	Screw Hole (mm)	Hole Number
F15-RMA/PL	20.3*24	35	5	25	Φ3.5	2
		500	50	200	Φ3.5	3
		1000	100	200	Φ3.5	5
		2000	100	200	Φ3.5	10

6. Appendix

6.1 Certificate

Certificating Type	Testing Organization	Certificate Serial Number	Report Reference
UL 2108	UL	20180801-E360029	E360029-20130322
CE-EMC	SGS	SZEM1712012372LMV	SZEM171201237201

6.2 Third-Party Test Report

Testing Item	Testing Organization	Report Number
RoHS	SGS	CANEC1815144401
		CANEC1815146401
IP68: Screw type	TUV SUD	68.140.12.136.02
IP68: Clasp type	SGS	GZES140200135301
		GZES140200135401
		GZES140200135501
		GZES140200135701
		GZES140200135801
IPX8: Molding type	SGS	SZES141200357301
		SZES141200357401
		SZES141200357501
IPX8: Snap type	SGS	GZES160600792031
Flame retardant	TUV SUD	68.140.13.068.01
IPX8: Dual Injection Moulding	SGS	SZES171001697401
		SZES171202089731
Safely: IEC60598-1& IEC60598-2-21	LCS	LCS180307033BS
		LCS180307034BS
		LCS180307035BS
		LCS180307036BS
		LCS180307037BS

6.3 Reliability Test of Light

TESTING ITEM	PERFORMANCE	STANDARD/REFERENCE VALUE/DESCRIPTION
PHOTOMETRIC TESTING	Spectrum Analysis	IES LM 79 (lumen, CCT, CRI, XY, SDCM, wave length)
	Photometric Distribution	IES LM 79(lumen intensity distribution & Lux diagram)
	Lumen Maintenance & Life Time	IES LM84 & IES TM28
TEMPERATURE RISE TESTING	Normal Temperature Test	UL1598 & UL2388 & IEC60598-1 & IEC60598-2-21
	Abnormal Operation Test	UL1598 & UL2388 & IEC60598-1 & IEC60598-2-21
MECHANICS & PHYSICS TESTING	Bending Test	Manufacturer-defined, 500 cycles
	Swing Test	UL2388, >750 cycles
	Tensile Test	Manufacturer-defined, > the weight of light in maximum connection length with both ends feed
	Twist Test	Manufacturer-defined, >200 cycles
	Ball Impact	UL1598 & UL2388 & IEC60598-1 & IEC60598-2-21
WEATHERING TESTING	IK07 IK08	IEC62262
	Swimming Pool Water Immersion Test	GB9667, PH6.8-7.6, free chlorine 0.3-0.6mg/L
	Sea Water Immersion Test	IEC60598-1, Salinity 4%
	Salt Spray Test	IEC68-2-11
ENVIROMENT TESTING	Outdoor Exposure	Manufacturer-defined
	Flame Resistant Test	UL94
	UV Exposure Test	ASTMG 154 , ISO 4892-3 , UVA@340nm
	IPX5 IPX6 IPX7 IPX8	IEC60529
ENDURANCE & THERMAL TEST LAB	Temperature Shock Test	Manufacturer-defined , -40°C-60°C (typical temperature range)
	Constant Temperature Test	Manufacturer-defined , 70°C (typical temperature)

6.4 (X,Y) Chromaticity Diagram

