DECORATIVE LUMINAIRE


RING

The aluminium frame of the lamp has undergone a bending process, resulting in a beautiful and smooth form. Light circles can be hung on the ceiling. RING is available in two standard dimensions of 60 and 80 cm diameter. LED light can be dim, pleasantly warm or smoothly changed into a neutral or cool white colour that supports focus and work. The lamp can be used as main or decorative lighting.




Technical data

Power16W19WInput voltage12V DC or 24V DC12V DC or 24V DCBeam angle120°120°Colourmonocolour or CCTmonocolour or CCTColour temperature3000K, 4000K, 5000K3000K, 4000K, 5000KLuminous flux790 lm1040 lmLight sourceLEDLEDAmbient temperature rangefrom -20°C to 40°Cfrom -20°C to 40°CDimmingdimmabledimmableIP codeIP40IP40Colour rendering index (CRI)80, 90 (depends on the LED strip)80, 90 (depends on the LED strip)Energy classA++A++DiffusorOpal, PMMAOpal, PMMAControlRemote controllerRemote controllerMaterials, coloursAluminium black or silverAluminium black or silver		RING 60	RING 80
Beam angle 120° 120° 120° Colour monocolour or CCT monocolour or CCT Colour temperature 3000K, 4000K, 5000K 3000K, 4000K, 5000K Luminous flux 790 lm 1040 lm Light source LED LED Ambient temperature range from -20°C to 40°C from -20°C to 40°C Dimming dimmable dimmable IP code IP40 IP40 Colour rendering index (CRI) 80, 90 (depends on the LED strip) Energy class A++ A++ Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Power	16W	19W
Colour monocolour or CCT Colour temperature 3000K, 4000K, 5000K Luminous flux 790 lm Light source LED Ambient temperature range from -20°C to 40°C Dimming dimmable IP code IP40 Colour rendering index (CRI) Energy class A++ Diffusor Opal, PMMA Control monocolour or CCT above, 5000K, 4000K, 5000K from -20°C to 40°C Above A++ A++ Diffusor Opal, PMMA Opal, PMMA Remote controller	Input voltage	12V DC or 24V DC	12V DC or 24V DC
Colour temperature 3000K, 4000K, 5000K 3000K, 4000K, 5000K Luminous flux 790 lm 1040 lm Light source LED LED Ambient temperature range from -20°C to 40°C from -20°C to 40°C Dimming dimmable dimmable IP code IP40 IP40 Colour rendering index (CRI) 80, 90 (depends on the LED strip) 80, 90 (depends on the LED strip) Energy class A++ A++ Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Beam angle	120°	120°
Luminous flux790 lm1040 lmLight sourceLEDLEDAmbient temperature rangefrom -20°C to 40°Cfrom -20°C to 40°CDimmingdimmabledimmableIP codeIP40IP40Colour rendering index (CRI)80, 90 (depends on the LED strip)80, 90 (depends on the LED strip)Energy classA++A++DiffusorOpal, PMMAOpal, PMMAControlRemote controllerRemote controller	Colour	monocolour or CCT	monocolour or CCT
Light sourceLEDLEDAmbient temperature rangefrom -20°C to 40°Cfrom -20°C to 40°CDimmingdimmabledimmableIP codeIP40IP40Colour rendering index (CRI)80, 90 (depends on the LED strip)80, 90 (depends on the LED strip)Energy classA++A++DiffusorOpal, PMMAOpal, PMMAControlRemote controllerRemote controller	Colour temperature	3000K, 4000K, 5000K	3000K, 4000K, 5000K
Ambient temperature range from -20°C to 40°C from -20°C to 40°C Dimming dimmable dimmable IP code IP40 IP40 Colour rendering index (CRI) 80, 90 (depends on the LED strip) 80, 90 (depends on the LED strip) Energy class A++ A++ Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Luminous flux	790 lm	1040 lm
Dimming dimmable dimmable IP code IP40 IP40 Colour rendering index (CRI) 80, 90 (depends on the LED strip) 80, 90 (depends on the LED strip) Energy class A++ A++ Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Light source	LED	LED
IP code IP40 IP40 IP40 Colour rendering index (CRI) 80, 90 (depends on the LED strip) 80, 90 (depends on the LED strip) Energy class A++ A++ Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Ambient temperature range	from -20°C to 40°C	from -20°C to 40°C
Colour rendering index (CRI) 80, 90 (depends on the LED strip) 80, 90 (depends on the LED strip) Energy class A++ A++ Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Dimming	dimmable	dimmable
Energy classA++A++DiffusorOpal, PMMAOpal, PMMAControlRemote controllerRemote controller	IP code	IP40	IP40
Diffusor Opal, PMMA Opal, PMMA Control Remote controller Remote controller	Colour rendering index (CRI)	80, 90 (depends on the LED strip)	80, 90 (depends on the LED strip)
Control Remote controller Remote controller	Energy class	A++	A++
	Diffusor	Opal, PMMA	Opal, PMMA
Materials, colours Aluminium black or silver Aluminium black or silver	Control	Remote controller	Remote controller
•	Materials, colours	Aluminium black or silver	Aluminium black or silver
Set up Steel cord wires for hanging Steel cord wires for hanging	Set up	Steel cord wires for hanging	Steel cord wires for hanging



RING 60




RING 80

Dimensions [mm]









RING 60 RING 80

